



Pyrotexx® IS - Fire Sleeve

Pyrotexx® fire sleeve is used to protect employees from burns due to hot hoses or pipes, while reducing costly heat energy losses. It provides excellent resistance to intense radiant heat, sparks, molten metal splashes and occasional flame.

Technical Data

Carrier material	Braided glass fiber
Coating	Silicone
Temperature Range	-60°C up to +260°C short term exposure up to 1.100°C max. short term exposure: 1.600°C
Properties	Very good flexibility Water and oil resistant

Fields of application

- Metallurgy
- Incineration plants
- Steam and oil lines
- Injection molding machines
- Drawing presses

Product details

DN	product number	roll length m
6	4470 0 006	20
8	4470 0 008	20
10	4470 0 010	20
13	4470 0 013	20
15	4470 0 015	20
19	4470 0 019	20
25	4470 0 025	20
30	4470 0 030	20
32	4470 0 032	20
35	4470 0 035	20
40	4470 0 040	20
45	4470 0 045	20
50	4470 0 050	20

DN	product number	roll length m
57	4470 0 057	20
60	4470 0 060	20
64	4470 0 064	20
70	4470 0 070	20
76	4470 0 076	20
80	4470 0 080	15
85	4470 0 085	15
90	4470 0 090	15
95	4470 0 095	15
100	4470 0 100	15
110	4470 0 110	10
125	4470 0 125	10

