



Fire sleeve - F88 SC · Model DV

Silicone-coated fire sleeve with hook-and-loop fastener for subsequent assembly.

Technical data

Source material
Fastening

Fire sleeve F88 SC
Hook-and-loop fastener made of stainless steel or brass, nickel-plated
Dimensions 22 x 13 mm, height 16 mm
Distance between hook-and-loop fasteners: 100 mm

Key characteristics

- excellent mechanical protection
- halogen-free flame protection
- free of softeners
- free of heavy metals
- REACH-compliant

Technical values

Kevlar® strips type KV290 to prevent thermal bridges on metal fasteners as well as edge protection

Available sizes

Available lengths on demand, maximum 25 m
not a stock item; delivery time after consultation

Product details

DN	product number	approx. weight g/m
30	4499 7 030	640
40	4499 7 040	740
50	4499 7 050	840
60	4499 7 060	940
70	4499 7 070	1045
80	4499 7 080	1160
90	4499 7 090	1255
100	4499 7 100	1350
110	4499 7 110	1450
120	4499 7 120	1560

DN	product number	approx. weight g/m
130	4499 7 130	1670
140	4499 7 140	1750
150	4499 7 150	1870
160	4499 7 160	1970
170	4499 7 170	2070
180	4499 7 180	2065
190	4499 7 190	2270
200	4499 7 200	2370
220	4499 7 220	2590
250	4499 7 250	2880

Status as of 05/2023 · Technical changes in the course of development reserved.

