



Fire sleeve - F88 SC · Model KK

Silicone-coated fire sleeve with spherical head fastener for subsequent assembly.

Technical data

Source material
Fastening

Fire sleeve F88 SC
Spherical head made of brass, nickel-plated
dimensions 20 mm diameter, height 10 mm
Distance between spherical heads: 100 mm

Technical values

Kevlar® strips type KV290 to prevent thermal bridges on metal fasteners

Available sizes

Available lengths on demand, maximal 25 m
not a stock item;
Delivery time after consultation

Key characteristics

- excellent mechanical protection
- halogen-free flame protection
- free of softeners
- free of heavy metals
- REACH-compliant

Product details

DN	product number	approx. weight g/m
30	4499 8 630	520
40	4499 8 605	675
50	4499 8 607	775
60	4499 8 609	870
70	4499 8 611	990
80	4499 8 613	1100
90	4499 8 615	1195
100	4499 8 617	1290
110	4499 8 619	1390
120	4499 8 621	1500

DN	product number	approx. weight g/m
130	4499 8 623	1610
140	4499 8 625	1690
150	4499 8 627	1810
160	4499 8 629	1910
170	4499 8 631	2005
180	4499 8 633	1205
190	4499 8 635	2220
200	4499 8 637	2330
220	4499 8 639	2520
250	4499 8 641	2815

Status as of 05/2023 · Technical changes in the course of development reserved.

