



## Fire sleeve - F88 SC · Model KV

Silicone-coated fire sleeve with Velcro fastener for subsequent assembly.

**Certifications** DIN EN 45545-2:2020 R22/R23-HL3

### Technical data

<b>Source material</b>	Fire sleeve F88 SC
<b>Fastening</b>	Velcro fastener flame retardant, DIN 75200 / ISO 3795
<b>Technical values</b>	Velcro fastener width to DN90 = 30 mm; from DN100 = 38 mm Kevlar® strips type KV290 as edge protection
<b>Available sizes</b>	Available lengths on demand, maximum 25 m not a stock item; delivery time after consultation

### Key characteristics

- excellent mechanical protection
- halogen-free flame protection
- free of softeners
- free of heavy metals
- REACH-compliant
- Puncture strength DIN EN 60684 >10kv

### Product details

DN	product number	approx. weight g/m
30	4499 8 030	520
40	4499 8 040	615
50	4499 8 050	715
60	4499 8 060	810
70	4499 8 070	930
80	4499 8 080	1040
90	4499 8 090	1135
100	4499 8 100	1230
110	4499 8 110	1330
120	4499 8 120	1440

DN	product number	approx. weight g/m
130	4499 8 130	1550
140	4499 8 140	1630
150	4499 8 150	1750
160	4499 8 160	1850
170	4499 8 170	1945
180	4499 8 180	2045
190	4499 8 190	2160
200	4499 8 200	2270
220	4499 8 220	2460
250	4499 8 250	2755

